


UTP Category 6 Cables

| Content of Data Sheet | | |
|-----------------------|---|---|
| Product model | CABLE-CAT6-BU | |
| Product specification | Quality verified by latest standard AS/CA S008:2020 | |
| Test Standard | ISO/IEC11801、TIA-568-C.2 | |
| Conductor | Material | Solid-Bare Copper |
| | AWG | 24 |
| | Nom.O.D.(mm) | 0.52±0.03 mm |
| | DC resistance | ≤95 Ω/km |
| Insulation | Material | HDPE |
| | Thickness | 0.2±0.02 mm |
| | Diameter | 0.93±0.05 mm |
| | Color | Blue/White- Blue Orange/White-Orange |
| Pitch | Offset pitch | ≤20 mm |
| | Cable pitch | ≤120 mm |
| Sheath | Material | PVC(complies RoHS/REACH) |
| | External O.D. | 5.8±0.3 mm |
| | Color | Blue |
| | Tensile strength | >13.5 Mpa |
| | Thickness | 0.6±0.05 mm |
| Surface Printing | Letter height | 3.0±0.3 mm |
| | Color | Black |
| | Print error & Space | 1±0.005 m |
| | Case number | Yes |
| Packing | Packing | Carton + Plastic shaft |



| | | | | |
|---------------------|-------------------------|-------------------|--|-----|
| | Once packing dimension | 331mm*255mm*338mm | | |
| | Twice packing dimension | 550mm*350mm*360mm | | |
| | Twice packing quantity | 2 cases | | |
| Packing length | 305±1m | | | |
| Rip-cord | Yes | Crossing backbone | | Yes |
| Ambient temperature | -20°C ~ 60°C | | | |

Zhejiang Uniview Technologies Co.,Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.